

** CLEARANCE REQUIRED FOR
THERMAL MOVEMENT

2" LONG PIECE OF 3/32" X 1"
ROLL TAPE SEALANT
(@ GUTTER STRAP LOCATIONS)

3/16" X 7/8" DOUBLE BEAD
TAPE SEALANT (PIGTAIL)

3/8" OFFSET CLEAT

GUTTER STRAP
(@ 3'-0" O.C.)

43D POP RIVET
(2 PER STRAP)

GUTTER

#10-12 X 1" TYPE A PANCAKE
HEAD FASTENER (@ 1'-0" O.C.)
(MUST GO THROUGH STRAP)

WOOD BLOCKING
(NOT BY MCELROY)

DOWNSPOUT

FASCIA BOARD
(NOT BY MCELROY)

SUPPORT
(NOT BY MCELROY)

9" (MAX.)

**

3/32" X 1" ROLL TAPE
SEALANT (CONT. ALONG EAVE)

#14-10 X 1 1/2" HWH TYPE A
FASTENER (2 PER CLIP)

MAXIMA LOW FLOATING
CLIP

MAXIMA ADV PANEL

THERMAL SPACER

APPROVED HIGH TEMP. PEEL & STICK
UNDERLAYMENT UNDER EAVE TRIM AND
FOR FIRST 3'-0" FROM EAVE, LAPPED
OVER OFFSET CLEAT. #30 FELT
THEREAFTER. (NOT BY MCELROY)

NOM. 1/2" (MIN.) NAILABLE
AND RIGID INSULATION
(NOT BY MCELROY)

VAPOR BARRIER
(RECOMMENDED)
(NOT BY MCELROY)

22GA. METAL DECK
(NOT BY MCELROY)

ROOF LINE
(NOT BY MCELROY)

#10-12 X 1" TYPE A PANCAKE
HEAD FASTENER (@ 5'-0" O.C.)

*NOTE: SLIDING SNOW AND ICE COULD
CAUSE DAMAGE TO GUTTER SYSTEM.